

Clip-on profile roller shutter box EJOT® Pro ASP-R

ASP-R06/01: 8805040001 | ASP-R10/01: 8805040002

Application

For the formation of a precise and stable plaster border with targeted water flow. Using the clip-on profile prevents direct contact between the roller shutter box and the plaster coating and any movements that occur are partially compensated for

Properties

Targeted drainage of water; precise and clean plaster finish; better plaster grip due to grooved surface

Storage and transport

lying on the entire surface; dry and frost-free; not above 50 °C; no direct sunlight

Dimensions and packaging	
Bar length [m]	2.4
Pieces / cardboard box	30
Running meter / cardboard box	72
Cardboard box / pallet	44
Running meter / pallet	3,168
Pallet height [m]	1.3

Basic profile	
Raw material	Rigid PVC – free from lead and cadmium – REACH compliant
Tolerances	Profile general tolerances 2A according to DIN 16941
Colour fastness	According to DIN EN 20105-A03 – compliance level 2

Mesh	
Glass fiber fabric	R131 or comparable (certified on the basis of EAD 040016-01-0404 / EAD 040083-00-0404)
Fabric grammage [g/m²]	160
Mesh size [mm]	4 x 4
Fabric colour/print	White neutral
Fabric width [cm]	12.5 ± 5 %
Fabric fastening	welded

