

Cavity wall repair anchor VSD



Application range

- > For fast and adhesive-free subsequent installation of curtain walls
- > For load-bearing shells made of concrete, solid brick and perforated brick

Characteristics

- > Building authorities-approved anchor for subsequent installation of curtain walls
- > Double expansion wall anchor: simultaneous embedment in load-bearing wall and curtain wall
- > Clean and fast installation (no mortar required)
- > Universal expansion zone: secure installation into concrete load-bearing shells, solid and perforated brick
- > The use of A4 stainless steel screws guarantees corrosion protection
- > 100% installation control
- > Temperature-independent installation times
- > Can be installed at 0°C


Cross references

Cleaning brush
Blow-out pump
Tool belt
Hammer drill SDS-plus
Cordless screwdriver ASCM
Cordless hammer drill
Bit hexalobular TX25
Duster Expert SDS plus®



Notice

The VSD cavity wall repair anchor enables the subsequent renovation of double-sheet masonry. Advanced corrosion or a complete lack of wire anchors can lead to decreased stability of the curtain wall and possibly cause considerable physical injury. In particular curtain walls made before 1979 should be subject to further inspection. When renovating the outer facade, the stability of the curtain wall must be verified. The EJOT® VSD is a particularly cost-effective solution for subsequent installation between load-bearing shell and curtain wall.

Technical specifications



Certifications



Product online



Order description	Length l_d [mm]	Drill hole depth t_s ≤ [mm]	Distance a_z [mm]	Curtain wall h_a ≥ [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
Anchors with A4 stainless steel screws (-E)								
VSD-8Ux205-E	205	215	0–20	115	100		8765205600	4061245010670
VSD-8Ux225-E	225	235	20–40	115	100		8765225600	4061245010663
VSD-8Ux245-E	245	255	40–60	115	100		8765245600	4061245010656
VSD-8Ux265-E	265	275	60–80	115	100		8765265600	4061245010649
VSD-8Ux285-E	285	295	80–100	115	100		8765285600	4061245010632
VSD-8Ux305-E	305	315	100–120	115	100		8765305600	4061245010625