

EJOT® concrete screw JBS-R-7.5



Application range

- > To fix roofing membranes to concrete substructures
- > For combination with EJOT stress plate EcoTek 50


Properties

- > Case-hardened steel
- > Climadur coated – high-quality coating to improve corrosion protection (15 Kesternich cycles, DIN 50018, 1997)

Applications



Technical data



Cross reference

Stress plate EcoTek 50
 Bit extension
 Hammer drill SDS plus
 Bit hexalobular TX

Certifications



Online shop



Order description	Length [mm]	Diameter [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JBS-R 7.5x80	80	7.5	100		2 231 080 609	4061245020884
JBS-R 7.5x120	120	7.5	100		2 231 120 609	4061245020877
JBS-R 7.5x150	150	7.5	100		2 231 150 609	4061245020860
JBS-R 7.5x210	210	7.5	100		2 231 210 609	4061245020853
NEW JBS-R 7.5x300	300	7.5	100		2 231 300 609	4061245062501

Compatibility acc. to ETA-07/0013

	HTV 82/40	HTE 82/40	HTV 82/40 TK	HTV 82/40 F	HTV 40 RU	HTK 2G 50xL	HTK 2G 75xL	EcoTek 50	EcoTek-T 50	HTK-S	Flat roof profile FP
JBS-R-7.5								X	X		