

## Centring grommet F (fixed point)



### Cross references

JF3-LT-2-5.5x30  
 JT3-LT-3-5.5x30  
 JT4-LT-3-5.5x25  
 JT4-LT-2/6-6.0x50

### Application range

- > For fastening facade claddings in combination with LT screws with head diameter 16 mm
- > To form fixed points

### Properties

- > Grey coloured plastic
- > For panel thicknesses 2 / 4 / 6 / 8 mm
- > UV-resistant

### Advantages

- > All holes in the facade cladding are produced with the same diameter (11 mm), which can be done efficiently at the shop floor
- > No rivet installation gauge, no drilling gauge necessary
- > Fast assembly in combination with LT screws
- > Easily revisionable panel fastening
- > The 0.5 collar of the grommet prevents direct contact between screw head and panel surface
- > The hole in the middle serves for the centred positioning of the screw

### Notice

Usability of grommets and LT screws must be agreed with the respective panel manufacturer. Please note the respective approval for the exterior wall cladding and the assembly instructions of the manufacturer.

### Product online



Order description	Internal hole diameter [mm]	Pre-drilling diameter [mm]	Panel thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
EJOT centring grommet Ø 11/2 F	5.8	11.0	2.0	500		3010005700	4061245010212
EJOT centring grommet Ø 11/4 F	5.8	11.0	4.0	500		3010009700	4061245018478
EJOT centring grommet Ø 11/6 F	5.8	11.0	6.0	500		3010011700	4061245018454
EJOT centring grommet Ø 11/8 F	5.8	11.0	8.0	500		3010007700	4061245018492