

Anchor rod AST / threaded rod



Cross references

Mortar cartridge USF
Mortar cartridge USF winter
Mesh sleeve
Cordless hammer drill ABH
Hammer drill SDS plus®
Cleaning brush
Blow-out pump

Application range

- > For embedment in concrete and solid brick
- > For embedment in perforated brick in combination with mesh sleeve

Properties of AST steel

- > Anchor rod: property class 5.8 acc. to EN ISO 898-1
- > Nut: property class 5 acc. to EN ISO 898-2
- > Washer: acc. to EN ISO 7089

Properties of AST A4 stainless steel (1.4401 / 1.4571)

- > Anchor rod: EN 10088; property class 70 (A4-70) acc. to EN ISO 3506
- > Nut: EN 10088; property class 70 (A4-70) acc. to EN ISO 3506
- > Washer: acc. to EN 10088

Notice

To determine the characteristic load-bearing capacity in concrete or masonry, the ETAs of the chemical mortars in the Multifix range must be observed.

Technical specifications



Technical specifications

Threads	Embedment depth in concrete ≥ [mm]	Embedment depth in solid brick ≥ [mm]	Drill hole depth ≥ [mm]
M10	60	90	12

Product online



Order description	Threads	Length [mm]	PU [pieces]	Price/100 piece [EUR]	Article number	EAN
Anchor rod AST, zinc-plated steel						
AST M10x130-V	M10	130	10		9570910130	4061245010588
AST M10x170-V	M10	170	10		9570910170	4061245010571
Anchor rod AST, A4 stainless steel						
AST M10x110-E	M10	110	10		9571910110	4061245061597
AST M10x130-E	M10	130	10		9571910130	4061245010472
AST M10x170-E	M10	170	10		9571910170	4061245010465

Further lengths upon request

