

NEW T-FAST® Plus wood screw JW4 countersunk head**Cross references**



Cordless screwdriver ASCS QSW
Bit hexalobular TX

Application range

- > Fastening of non-pre-drilled or pre-drilled components made of wood, wood-based material and pre-drilled and pre-set steel components to non-pre-drilled or pre-drilled components made of solid wood, solid structural timber (KVH), glued-laminated timber (BSH), solid wood panels, laminated veneer lumber (LVL), wood-based panels or cross-laminated timber
- > For weathered areas
- > Suitable for universal application

Characteristics

- > Stainless steel CRC II or stainless steel A2 with dry lubricant
- > Countersunk (STR) head with milling ribs on the underside makes it easier to countersink the head for surface-fixed installation
- > The end mill at the transition to the non-threaded fastener shaft reduces the installation torque and simplifies the installation process (from 50 mm shaft length)
- > Partial thread for tightening the components to be fastened
- > Optimised thread geometry for improved prevention of screw over-tightening
- > T-FAST® Plus point geometry facilitates the screwing-in process through quick point biting, low screwing-in torque and efficiently reduced wood splitting

**Applications****Technical specifications****Certifications****Product online**

Order description	d [mm]	l [mm]	l ₀ [mm]	d _h [mm]	drive	PU [pieces]	Price/100 [EUR]	Article number	EAN
d 4.5 – partial threaded screw									
JW4-2-Plus-STR-4.5X50/30 S TX20	4.5	50	30	9.0	TX20	200		3820000466	4061245123738
JW4-2-Plus-STR-4.5X60/35 S TX20	4.5	60	35	9.0	TX20	200		3820000467	4061245123745
JW4-2-Plus-STR-4.5X70/40 S TX20	4.5	70	40	9.0	TX20	200		3820000468	4061245123752
JW4-2-Plus-STR-4.5X80/40 S TX20	4.5	80	40	9.0	TX20	200		3820000469	4061245123769
d 5.0 – partial threaded screw									
JW4-2-Plus-STR-5.0X50/30 S TX20	5.0	50	30	10.0	TX20	200		3820000470	4061245123776
JW4-2-Plus-STR-5.0X60/35 S TX20	5.0	60	35	10.0	TX20	200		3820000471	4061245123783
JW4-2-Plus-STR-5.0X70/40 S TX20	5.0	70	40	10.0	TX20	200		3820000472	4061245123790
JW4-2-Plus-STR-5.0X80/40 S TX20	5.0	80	40	10.0	TX20	200		3820000473	4061245123806
JW4-2-Plus-STR-5.0X90/45 S TX20	5.0	90	45	10.0	TX20	100		3820000474	4061245123813
JW4-2-Plus-STR-5.0X100/60 S TX20	5.0	100	60	10.0	TX20	100		3820000475	4061245123820
JW4-2-Plus-STR-5.0X120/70 S TX20	5.0	120	70	10.0	TX20	100		3820000476	4061245123837
d 6.0 – partial threaded screw									
JW4-2-Plus-STR-6.0X50/30 S TX30	6.0	50	30	12.0	TX30	200		3820000477	4061245123844
JW4-2-Plus-STR-6.0X60/35 S TX30	6.0	60	35	12.0	TX30	200		3820000478	4061245123851
JW4-2-Plus-STR-6.0X70/40 S TX30	6.0	70	40	12.0	TX30	200		3820000479	4061245123868
JW4-2-Plus-STR-6.0X80/40 S TX30	6.0	80	40	12.0	TX30	200		3820000480	4061245123875
JW4-2-Plus-STR-6.0X90/45 S TX30	6.0	90	45	12.0	TX30	100		3820000481	4061245123882
JW4-2-Plus-STR-6.0X100/60 S TX30	6.0	100	60	12.0	TX30	100		3820000482	4061245123899