

## Stress plate HTK-S



### Cross references

- DABO® TKR-4.8
- DABO® TKE-4.8
- DABO® TKR-4-4.8
- DABO® VHT-R-4.8
- DABO® VHT-E-4.8
- Bit extension with spring pin
- Hip belt flat roof

### Application range

- > To fix roofing membranes and insulating material to substructures made of steel, trapezoidal aluminium profile, timber and wood-based material in combination with flat roof profile FP
- > To reduce thermal bridges
- > For special requirements of resistance to imposed loads


### Properties

- > High-grade plastic material
- > Telescope design for resistance to imposed loads


### Note

For combination with EJOT DABO® screws

### Applications



### Technical specifications



### Certifications



Conforms to the requirements according to VOB and the application class K2 according to DIN 18531 regarding the corrosion resistance

### Product online



Order description	Effective shaft length L [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
HTK-S-20x90	90	150		8598090010	4061245011110
HTK-S-20x140	140	150		8598140010	4061245011103

### Compatibility acc. to ETA-07/0013

HTK-S	SW 8 RT-4.8	SW 8 ET-4.8	TKR-4.8	TKE-4.8	TKR-4-4.8	VHT-R-4.8	VHT-E-4.8	JT2-ST-2-6.0	JT2-ST-2-6.8	JT3-ST-2-6.0	FBS-R-6.3	JBS-R-7.5	FPS-E-8.0	SDF-S-10H-E	SDP-S-10G-E
			X	X	X	X	X								