

EJOPLAST joint sealant



Application range

- > For sealing the DEKTITE® pipe flashings

Properties

- > Single-component universal sealant based on polycarboxylic acid copolymeric base
- > ACE 7 adheres to almost all surfaces (e.g. Steel, aluminium, copper, brass, glass, wood, ceramic, bitumen, concrete, masonry, plaster, plexiglas, tiles, roof tiles, polyester, roofing paper, etc.)
- > Immediately rainproof - workable in the rain
- > Excellent weather and UV resistance

Technical specifications

Skin formation time at 23 °C/50 % rLf [min]	~ 1
Installation temperature: from/to [°C]	+ 5/ + 35
Viscosity at 23 °C	pasty
Density at 23 °C according to ISO 1183-1 [g/cm³]	~ 1.1
Permitted total deformation [%]	10
Temperature resistance from/to [°C]	- 20/ + 80
Shelf life at 23 °C/ 50 % rLf [months]	24*
Storage temperature from/to [°C]	0/ + 30
Volume shrinkage according to ISO 10563 [%]	~ 20

*From production

Product online



Order description	Contents [ml]	Colour	PU [pieces]	Price/1 [EUR]	Article number	EAN
EJOPLAST 310 ml clear	310	clear	1		8200001100	4061245093901