Self-drilling screw JT2-WD-5-5.5

Application range

> Special screw for fastening wood to steel substructures up to a thickness of 5 mm

Properties

> Case-hardened steel, protected against corrosion
> The wings widen the drill hole in the wood component to be fastened in order to prevent forced feed. They break off as soon as they touch the steel substructure. This prevents the wood to be fastened from being pushed away from the substructure.

Notice

To ensure shearing of the wings, the material thickness of the steel substructure must be at least 2.5 mm. The screw is not suitable for fastening OSB boards.

Applications

Technical specifications



Cross references

Cordless screwdriver ASCM QSW
Bit hexalobular TX25
Bit holder

Installation process

Product online

Order description	Length [mm]	Thread length [mm]	Clamping thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JT2-WD-5-5.5x50	50	30	12–35	200		7289206601	4061245014388
JT2-WD-5-5.5x60	60	30	22–45	200		7289207601	4061245014371
JT2-WD-5-5.5x80	80	60	12–65	200		7289208601	4061245014364
JT2-WD-5-5.5x100	100	60	32–85	200		7289202601	4061245038537

Further lengths on request

EJOT SE & Co. KG · Market Unit Construction · In der Stockwiese 35 · 57334 Bad Laasphe · Germany
T +49 2752 908-0 · F +49 2752 908-731 · construction@ejot.com · www.ejot.com/construction